

orto alresa

Centrifuges and laboratory products

info@ortoalresa.com

www.ortoalresa.com

+34 91 884 40 16



General applications: Centrifuges micro

BIOCEN 22

BIOCEN 22

LED

Centrifuges micro: Biocen 22



IVD CE

Max. capacity: 24 x 2 ml./ 12 x 5 ml.

Max. speed: 21.885 xg / 15.000 RPM

The Biocen 22 centrifuge is our offer for users requiring a microcentrifuge with possible applications for microhematocrit and microtubes. Its small size, good performance and great versatility make it an essential tool. It gives the user complete control from the beginning of the process and many values can be customised according to the processes. Built to ensure the minimum increase of temperature inside the chamber due to the high-speed centrifugation process.

We know how important a sample is as a part of a process and therefore we try to interfere as little as possible to avoid interference and ensure a precise, exact, reliable and rapid result.

Features

LED screen:

- Shows RPM/ RCF and time.
- Speed programming in 50 RPM/ 10 xg steps.
- Timer countdown/up from "0" or at "set RPM/ RCF" for reproducible tests.
- Timer from 1 to 99 min. programmable in 1 min. steps and hold position.
- Acceleration and deceleration control in 3 steps: fast, soft and free.
- Acoustic and visual messages on screen warning the user the equipment status.

Easy to use

- Microprocessor controlled.
- Induction motor maintenance free (brushless).
- Rotors list on memory.
- Noise level: below 60 dB.
- Start, stop, open lid and short spin with adjustable speed buttons.
- Option of free/locked adjustment of RPM/ RCF along the run.
- Automatic open lid, programmable.
- Low height for easy access.
- Last values remain in memory.
- Over-speed protection.

Safety

- Lid provided with security systems:
 - Automatic lid lock system, motorized.
 - Emergency lid-lock release.
 - Locking and protection against opening along the run.
 - Lid dropping protection.
 - Port in the lid for calibration and operation checking.

- Unbalance detection and switch off.
- Protection safety ring between the centrifugation chamber and the housing.
- Chamber of centrifugation in stainless steel (easy cleaning).
- Rotors can be removed with the lid closed. Hermetic lids.
- Rotors and adapters autoclavable, easy to install by the user.
- Forced ventilation to reduce temperature increasing
- Automatic disconnection for energy saving, with deactivation option.

EU Directives: 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 98/79/EC.

Standards: EN 61010-1, EN 61010-2-101, EN 61010-2-020, EN 61326-2-6, EN 61326-1.

Versions

| | Dimensions (mm) (w x d x h) | | | Net weight (Kg) | Voltage (V) | Frecuency (Hz) | Consumption (W) |
|--------|--------------------------------|-----|-----|--------------------|----------------|-------------------|--------------------|
| CE 146 | 270 | 380 | 270 | 16 | 220-230 | 50-60 | 360 |
| CE 147 | 270 | 380 | 270 | 16 | 110-120 | 50-60 | 360 |

| Accessories | RT 227 | RT 228 | RT 229 | RT 254 |
|---------------|---|---|---|---|
| |  |  |  |  |
| | | (1) | | (2) |
| ROTOR | ANGLE FIXED 45 ° | HORIZONTAL | ANGLE FIXED 45 ° | ANGLE FIXED 45 ° |
| Max. capacity | 24x1,5-2 ml | 24x1,5x75 mm | 32x0,2 ml | 12 x 5 ml |
| RPM Max. | 15.000 | 15.000 | 15.000 | 15.000 |
| Radius (mm) | 82 | 87 | 55 | 87 |
| RCF Max. (xg) | 20.627 | 21.885 | 13.835 | 21.884 |

| SAMPLE VOLUME | ADAPTERS | | ADAPTERS | | ADAPTERS | | ADAPTERS | |
|---------------------------|----------|--------|----------|------|----------|------|----------|--------|
| | Tubes | Ref. | Tubes | Ref. | Tubes | Ref. | Tubes | Ref. |
| 5 ml. conical / screw cap | - | - | - | - | - | - | 12/6 | - |
| 1,5x75 mm. Capillaries | - | - | 24 | - | - | - | - | - |
| Microtubes 1,5-2 ml. | 24 | - | - | - | - | - | 12 | RE 506 |
| Microtubes 0,5-0,6 ml. | 24 | RE 305 | - | - | - | - | 12 | RE 507 |
| Microtubes 0,2-0,4 ml. | 24 | RE 304 | - | - | 32x0,2 | - | 12 | RE 508 |

(1) Includes microhaematocrit reader card.

(2) Available adapters for cryotubes.

orto
alresa
About centrifugation

info@ortoalresa.com

www.ortoalresa.com

+34 91 884 40 16

Álvarez Redondo S.A.
C/ Misericordia, 23.
Fax: +34 91 884 44 23
28864 AJALVIR Madrid (Spain)
Edition: January 2019.
Subject to modifications

