

Chest freezer ULT C75



- Low cost of ownership
- Limited maintenance
- On-site service
- Easily installable & movable
- Eco-friendly, HCFC-free Nature R refrigerant
- Efficient cyclopentane insulation
- Low energy consumption
- ISO 9001, 14001 & 18001 OHSAS Certified

Specifications

Technical

| | |
|---------------------------|------------------|
| Gross volume | 74 litres |
| Internal storage capacity | 71 litres |
| Temp. range | -60°C to -86°C |
| Temperature probes | 1 |
| Compressor | Embraco |
| Refrigerant | Nature R |
| Noise level | 53 dB |
| Power consumption 24/h | 5,10 kWh |
| Power consumption | 1.862 kWh / year |
| Voltage | 220V-240V |
| Frequency | 50 Hz |

Features

| | |
|---|--------|
| Audible & visual alarm | YES |
| Castors with brakes | 4 |
| Handle lock | YES |
| Inner lids | 1 |
| Defrost | Manual |
| Battery Backup | 50h |
| USB | NO |
| Data connection | NO |
| Digital controller with display | XR30CX |
| Data logging | NO |
| High/Low temperature alarm | YES |
| Analogue chart recorder | NO |
| Prepared for CO2 backup | YES |
| Prepared for external logging equipment | YES |

Dimensions

| | |
|-------------------|--------|
| Height | 895 mm |
| Height w. castors | 935 mm |
| Width | 550 mm |
| Depth | 645 mm |
| Gross weight | 57 kg |
| Net weight | 53 kg |

Internal dimensions

| | |
|-------------------|--------|
| Height | 465 mm |
| Width | 390 mm |
| Depth | 390 mm |
| Insulation | 80 mm |
| Insulation type | PUR |
| Internal humidity | <5 % |

| | |
|-------------|---------|
| Product no. | N113001 |
|-------------|---------|

ULT C75



Storage capacity

| Box height | No. of boxes | No. of racks | Total no. of boxes | Product no. |
|------------|--------------|--------------|--------------------|-------------|
| 50 mm | 8 | 5 | 40 | N311210 |
| 75 mm | 5 | 5 | 25 | N311310 |
| 100 mm | 4 | 5 | 20 | N311410 |